


FEATURES

- 3 Modern Bedrooms
- Open Modern Kitchen
- Top Security System
- Premium Location
- Luxurious Flnishes

Hanu ALSweifieh Close to Geneva Hotel








Hanu AlSweifieh Project

The following electrical systems are included in the project:

1ST SERVICE

Gas boiler



Gas boilers are the most popular choice for heating and hot water.

2nd SERVICE

Motion detector



The motion detector is an electrical device that detects nearby motion using a sensor (They are installed in the main entrance and the apartment bathroom).

3rd SERVICE

Water pump




Bottom and top water pump (Wilo).

The following electrical systems are included in the project:

4th SERVICE


Main internet distribution system



Collection of online travel portals or travel agencies (Fiber).

5th SERVICE

Central tv system



Central TV system is a mandatory solution for multi-room units.

6th SERVICE

Earth leakage protection system



Shock-prevention device used in electrical systems with high Earth impedance.

The following electrical systems are included in the project:

7th SERVICE

Electric shutters control



Easy control

8th SERVICE

Anti-theft system



Home security system

9th SERVICE

Water level meter



A water level meter is a typical equipment for measuring the exact level of water in groundwater observation wells.

The following electrical systems are included in the project:

10th SERVICE


Intercom



Smart audio and video intercom (Commax)


11th SERVICE

Switches



Italian Bticino sockets & Switches 12th SERVICE

Circuit Breakers



German Schneider Circuit Breakers

Commax Color TFT LCD High-**Tech Intercom Monitor CDV-70QT**

7" Inch Full Touch LCD Monitor





WIFI-enabled 7-inch smart full-touch video intercom display with smartphone connectivity. This intercom system can be used to extend your home access control to your phone. View and interact with visitors from all over the world.







DIAGRAM 2 wires wireless DDL MONITOR INTERPHONE CDV-70QT DP-4VHP DOOR CAMERA MONITOR INTERPHONE CDV-70QT DP-4VHP CCTV MAGNETIC SENSOR in door

PRODUCT FEATURES

- User friendly UI/UX
- Answer video call and open door by mobile app. (Wi-Fi based)
- Connectable with 1.0MP AHD door camera
- · Save the images by motion detection
- Built-in memory (50cuts, 640x360), SD card slot (128GB)
- Audio phone connectable (DP-4VHP)
- Digital door locks connectable (RF 447 MHz module option)
- 2 door cameras connectable 2 CCTV cameras connectable
- Magnetic sensor connectable for security mode (Mobile alarm function)
- Save the visitor's image and video

PRODUCT SPECIFICATION

| Power source | AC 100-240V, 50/60Hz (To SMPS) | |
|----------------|----------------------------------------------------------------|--|
| Display | 7 inch Full Touch LCD | |
| Mount type | Wall mounted type | |
| Memory | Built-in memory(50cuts, 640x360), SD card slot (128GB) | |
| Resolution | 1024 X 600 | |
| Network | Wi-Fi 2.4Ghz | |
| Camera | Up to AHD 1MP | |
| Wiring | Door camera : 4 wires Magnetic sensor(in door) : 2 wires x2 | |
| Dimension (mm) | 250(W) x 210(H) x 22(D) | |

HIKVISION CAMERA DS-2CE16H0T-ITPF

Specification

| Camera | | |
|--------------------------|---------------------------------------------------------------------------------------|--|
| Image Sensor | 5 MP CMOS image sensor | |
| Resolution | 2560 (H) × 1944 (V) | |
| Min. Illumination | Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR | |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s | |
| Lens | 2.8 mm, 3.6 mm, 6 mm fixed lens | |
| Horizontal Field of View | 85.5° (2.8 mm), 80.1° (3.6 mm), 57.1° (6 mm) | |
| Lens Mount | M12 | |
| Day & Night | IR cut filter | |
| Angle Adjustment | Pan: 0° to 360°; Tilt: 0° to 180°; Rotate: 0° to 360° | |
| Synchronization | Internal synchronization | |
| Frame Rate | PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps | |

















The switches that were placed in the project are Classia models, which are made by the Italian company BTicino International, a world authority on building electric and digital infrastructures.











Description

German Schneider 6 kg circuit breakers installed in the project can protect each line carrying energy or supplying appliances by selecting the appropriatesized circuit breaker, which will automatically disconnect in the event of a short circuit or a cable overload.
















Description

Bonex Lifts Elevator Company is the world's leading elevator producer, installer, and maintenance. Bonex full package customized elevators increase building safety and value. Elevators meet strict quality standards. wormed reduction gearless combined with three-phase AC-single Motor Speed. Imported from Italy with a capacity of 3.6 kW.

• Max Load: 480 kg

Capacity: 6 persons





Hanu AlSweifieh Project

MECHANICAL SYSTEMS

The following mechanical systems are included in the project:


1st SERVICE

Drainage systems




Drainage systems are installed in accordance with local construction requirements by a certified professional. 2nd SERVICE

Ventilation



Use ducts to circulate fresh air rather than depending on airflow through small holes or cracks. **3rd SERVICE**

Underfloor Heating




Underfloor heating is a method of heating a property by embedding strong and flexible tubing on the floor.

MECHANICAL SYSTEMS

The following mechanical systems are included in the project:

4th SERVICE

AC



Establishing split unit points

5th SERVICE

WATER



4000 L water with Wilo pump.

6th SERVICE

Fire fighting system



Fire alarm systems ensure the safety of your home 24/7, day or night (parking).



1. DRAINAGE SYSTEM

A drainage system consists of piping that conveys sewage, rainwater, or other liquid waste to the point of disposal in the sewer system or septic tank. Its main objective is to collect and remove wastewater and keep sewer gases out of the building.

2. VENTELATION SYSTEM:

BATHROOM EXTRACT FANS SILENT-100 DESIGN 3C Series

- A collection of axial hoods with airflow rates of approximately 85 m3/h for attachment to 100 mm-diameter round ducts.
- A flexible silent block system supports the motor, absorbing vibrations and enabling deficient noise levels.
- All fans are made of injection-molded plastic, have an automated shutter, a single-phase, 230V, 50Hz, Class B motor with thermal overload protection, and all these features.
- Each fan has Class II insulation, is IP45 rated, and can withstand air temperatures up to 40°C.









BATHROOM EXTRACT FANS SILENT-200 DESIGN 3C Series

Axial extractors with airflow rates of 175 m3/h for connection to circular ducting with a diameter of 120 mm. All the fans are injection-molded plastic with an automatic shutter and a single-phase 230V-50Hz class B low-consumption motor with thermal overload protection. All the fans have class II insulation, are IP45 rated, and can withstand temperatures up to 40°C.











3.UNDERFLOOR HEATING

We offer a highly efficient underfloor heating system installed to the highest standards by the United Pioneering Business Company. Underfloor heating networks from the Italian emmeti system and emmeti pipes with an aluminum layer were used. Furthermore, emmeti pipes were used for the illuminator and the rest of the underfloor heating network's requirements for central lines. Heating controllers with WIFI thermostat emmeti.













3. UNDERFLOOR HEATING

SINTESI MINI Wi-Fi

Wi-Fi-enabled electronic chronothermostat with weekly programming, installation on a flush-mounted box, and space for just two modules intended for controlling room temperature heating (for the winter). The free app, accessible through Google Play and the AppStore, enables complete control and programming from your smartphone or tablet. You can report any alarm situations by emailing the designated address.

WILO BOOSTER PUMP

Product advantages

- Stable water pressure due to automatic operation.
- High operational reliability and dry-running protection due to the integrated flow switch.
- Integrated thermal motor protection as standard
- Extremely low-noise operation.
- Corrosion protection through coated pump hydraulics.

Motor data

| Mains connection | 1~230 V, 50 Hz |
|----------------------------|----------------|
| Voltage tolerance | ±10 % |
| Rated power P ₂ | 0.2 kW |
| Rated current $I_{ m N}$ | 1.51 A |
| Rated speed n | 2900 1/min |
| Insulation class | F |
| Protection class | IPX4 |









For more information or to book a viewing tour get in touch with our marketing team.

00962795520443 00962799263003

http://www.taj-alsafa.com/

Taj alsafa@yahoo.com

